


HUAWEI FusionServer RH1288 V3



Copyright © Huawei Technologies Co., Ltd. 2014. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

Trademark Notice

 HUAWEI, and  are trademarks or registered trademarks of Huawei Technologies Co., Ltd.

Other trademarks, product, service and company names mentioned are the property of their respective owners.

General Disclaimer

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

HUAWEI TECHNOLOGIES CO., LTD.

Huawei Industrial Base
Bantian Longgang
Shenzhen 518129, P.R. China
Tel: +86-755-28780808
Version No.: M3-035260-20140904-C-2.0

www.huawei.com

HUAWEI TECHNOLOGIES CO., LTD.



HUAWEI FusionServer RH1288 V3

The HUAWEI FusionServer RH1288 V3 (RH1288 V3 for short) is a new-generation 1U dual-socket rack server. It achieves optimal balance of performance and density owing to optimal design. It is an ideal choice for enterprise computing-intensive applications, enterprise applications requiring both computing and storage resources, and cloud computing applications.

The RH1288 V3 servers provide the following features:

- High density and space-saving
- Integrated device management solution
- Flexible network configuration

New-generation E5-2600 v3 processors allow high performance

- Supports up to two Intel® Xeon® E5-2600 v3 processors. Each processor supports a maximum of 14 cores, a L3 cache of 35 MB, and 9.6 GT/s QuickPath Interconnect (QPI) speed.
- Supports up to sixteen 2133 MHz DDR4 DIMMs to provide a maximum memory capacity of 1 TB, meeting requirements of memory-demanding applications.
- Offers flexible networking. The server provides two or four GE ports or two 10GE ports without occupying PCIe slots, improving network availability.

Fine-grained power control improves emergency efficiency

- Uses 80 Plus Platinum power supply units (PSUs), meeting Energy Star specifications.
- Supports 460 W, 750 W, 800 W, and 1200 W PSUs, increasing energy efficiency.
- Uses temperature sensors in key components to monitor temperature in real time, and the fan modules implement intelligent speed adjustment based on the temperature to improve heat dissipation efficiency.
- Uses dynamic power conservation and power capping to safely limit the maximum server power consumption to a specified level without affecting services.

Professional management module provides comprehensive management

- Uses an independent iBMC module to implement Serial over LAN (SOL), remote KVM, and functions such as remote server startup and shutdown.
- Provides a wide variety of management interfaces, including the IPMI, CLI, HTTPS, SNMP, and WSMAN interfaces to facilitate integration with third-party systems.

Accurate fault locating facilitates efficient O&M

- Provides the "black box" function, similar to a flight recorder, to facilitate fault locating when the server collapses.
- Provides error codes through the server front panel to help fault locating.



RH1288 V3 (4 hard disks)



RH1288 V3 (8 hard disks)

RH1288 V3	
Form factor	1U rack server
Number of processors	1 or 2
Processor model	Intel Xeon E5-2600 v3 series processors
Memory	16 slots for DDR4 RDIMMs or LRDIMMs
Local storage	Supports two types of hard disk configurations: <ul style="list-style-type: none"> • Eight 2.5-inch SSDs or SAS or SATA HDDs • Four 3.5-inch SAS or SATA HDDs Supports Flash storage: <ul style="list-style-type: none"> • Dual SATA DOM • Dual-SD card
RAID	Supports RAID 0, 1, 10, 5, 50, 6, and 60 Uses a supercapacitor to protect RAID cache data from power failures Supports RAID state migration, RAID configuration memory, self-diagnosis, and remote web setting
Network ports	Provides two or four GE ports or two 10GE ports
PCIe expansion	Provides up to three PCIe slots
Fan	5 hot-swappable fan modules in N+1 redundancy. Each fan module has two counter-rotating fans.
PSU	Can be configured with two hot-swappable PSUs in redundancy and supports N+1 redundancy. The server supports the following PSUs: <ul style="list-style-type: none"> • 460 W or 750 W AC or DC PSU • 800 W -48 V DC PSU • 1200 W high-voltage DC PSU
Management	The on-board iBMC module supports Intelligent Platform Management Interface (IPMI), SOL, KVM over IP, and virtual media and provides a 1 Gbit/s RJ45 management network port supporting Network Controller Sideband Interface (NC-SI).
Supported OSs	CentOS Citrix XenServer Microsoft Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESXi
Power supply	110 V to 220 V AC 240 V to 380 V DC -48 V DC 5°C to 45°C (41°F to 113°F) NOTE: The RH1288 V3 servers operating at 40°C do not support SSDs, and the fault of one fan may affect CPU performance.
Certification	CE, UL, FCC, CCC, and RoHS
Installation suite	Guide rails Adjustable holding rails
Dimensions (W x D x H)	RH1288 V3 with 3.5-inch hard disks: 447 mm x 750 mm x 43.6 mm (17.60 in. x 29.53 in. x 1.72 in.) RH1288 V3 with 2.5-inch hard disks: 447 mm x 710 mm x 43.6 mm (17.60 in. x 27.95 in. x 1.72 in.)